

Honda GL1800 Power Plug Installation Instructions - Trunk Version

1. Open rear trunk. Remove both of the latches at the top of the trunk.
2. Remove the 15 phillips head screws that secure the inner black liner to the painted trunk.

Note: the screws for the inner liner and the latches are different. Do not interchange them.

3. Your installation location will vary based on what other accessories you have mounted in your trunk. The attached photo shows the ideal location.

Note: there are supports from the outer section of the trunk that can interfere with the installation of the Power Plug. Please be certain that your selected location will not interfere with these supports or the electrical box mounted on the inside of the trunk inner liner. Also make sure you take into consideration the depth of the Power Plug for the install.

4. Drill a 1 1/8" hole in the desired mounting location.
5. Insert the plug into the hole.
6. Connect the 2-pin plug from the Power Plug to the RED 2-pin connector inside the trunk lid.

Note: if you plug into the white connector, the Power Plug will only be hot when the brakes are on.

7. If you have the optional trunk light or lighted mirror, our Power Plug connectors will plug in-between the two.

Note: maximum current capacity is 5 amps. This plug is designed to power a cell phone or small audio device only.



Electrical Connection
3300F Rifle Range Dr
Knoxville, TN 37918
Phone 865-219-9192, Fax 865-219-9292
info@electricalconnection.com www.electricalconnection.com